



Advanced directional armchair from Quinti collection. The materials used are high level, comfortable and long lasting over time. Quinti is made in Italy, certified n° 290.058.V.

Base

1. Die-cast aluminum of 670mm "TREND"
2. cantilever structure, sled base

Castors

Double tread diam 50 mm, standard or rubberized, both can be free [standard] or self-braking. The feet in polyamide are interchangeable to the castors with the same locking pin at the base.

Elevation

All Quinti's gas columns are in accordance with the DIN4550 norm and they exceed the fourth level.

Mechanics

M5 the standard configuration of the chair supposes a tilt single lever mechanism with gas command, height and block in operative position. It has a wheel for the variation of the tilt rigidity. The main body is entirely made out of die-cast aluminum

M4 the point of rotation of this mechanism is advanced. The blocking lever allows the blocking process in 3 positions with a backstop system of the seat. It has a wheel for the variation of the tilting rigidity. The main body is entirely made out of shiny or black die-cast aluminum.

M3 [optional] Tilting Mechanism Plus advanced which allows the regulation of seating height, free tilt of backrest with block on 4 positions. Regulation of tilting tension, shiny aluminum.

Armrests

1. Couplet of armrests in mirror chromed steel
2. Couplet of armrests completely covered

Seat & Backrest


Seat and backrest are made of a monocoque multiplayer beech of 12 mm, upholstered and covered. Available both in the high and short versions.

Upholsters

Density of 50 and Thickness of 5 cm, resonated and double upholsters and covered .

AURORA **Quinti**[®]

DIMENSIONS



BIO-EXPO

CATEGORY 2

300 gr/mt2
100% Propitex FR batteriosattico
Classe 1UNI EN ISO 354:2003
100.000 +/- 10% Maltindale rubs

MELANGE

CATEGORY 3

390 g/lin.m
100% Trevira CS
Classe 1
80.000 +/- 10% Maltindale rubs

MERIT

CATEGORY 7

500g/lin.m
76% Poliestere Recycled
24% Poliestere
EN 1021-1/2
85.000 % Maltindale rubs

EXTREME

CATEGORY 2

350 gr/mtl
100% Xtreme FR
Classe , EN 1021-1/2
100.000 +/- 10% Maltindale rubs

JET

CATEGORY 3

365+/- 5% g/lin.m
100% Poliestere FR
Classe 1
80.000+/- 10% Maltindale rubs

PREMIUM /ELEGANCE

CATEGORY 7

100% Bovine leather Primo fiore
Spessore 1,2/1,4 mm
EN1021-1/2

LASER

CATEGORY 2

560 gr/mtl
100% Poliestere FR
Classe 1
80.000+/- 10% Maltindale rubs

PRO SYSTEM LEATHERETTE

CATEGORY 3

710 gr/mt2
Surface 93% PVC
Base Poliestere 28%
CLASSE1
100.000 RUBS

STEELCUT TRIO

CATEGORY 7

770 g/lin.m
90% New woolworsted, 10% Nylon
Classe 1, EN 1021-1/2
100.000 % Maltindale rubs

LEATHERETTE

CATEGORY 2

630 gr/mt2
83% PVC, 17% Syntetic
ISO 379-DIN75200-CSERF4/83 10%
Maltindale rubs

WOOL

CATEGORY 5

500 gr/mt2
75% Wool, 25% poliammide
Classe 1
100.000 Maltindale rubs

REMIK

CATEGORY 7

415 g/lin.m
90% New woolworsted, 10% Nylon
Classe 1, EN 1021-1/2
100.000 % Maltindale rubs

ERA

CATEGORY 3

448 gr/mtl
100% Trevira CS
Classe 1UNI EN ISO 354:2003
100.000 +/- 10% Maltindale rubs

LEATHER

CATEGORY 5/6

620 g/lin.m
100% Bovine Leather
Classe 1, EN 1021-1/2

DECONTRACTE' VELVET

CATEGORY 7

590 g/lin.m
19% CO, 61% PC, 10% PL, 10%VI
40.000 % Maltindale rubs

LASER PLUS

CATEGORY 3

630 gr/mtl
100% Poliestere FR Trevira
Classe1 , 4.000 +/- Maltindale rubs

PIED POULE

CATEGORY 6

550 g/lin.m
66% cotone, 34% Poliestere
35.000 % Maltindale rubs

VELVET

CATEGORY 8

600 g/lin.m
100.000 % PL Flameretardant

SOUL LEATHERETTE

CATEGORY 3

760 gr/mt2
Surface 100% POLIURETANO,
Base Poliestere 85%, 17% Cotone
EN1021-1/BS5852 PART 1
>100.000 EN ISO 5470-2

EUROPOST 2

CATEGORY 6

710 g/lin.m
63% PU, 16% CO, 21% PL
Ini1975 CLASSE1emme,UNI9175/FA
50.000% Maltindale rubs

SOFT LEATHER

CATEGORY 8

100% Bovine leather THICKNESS1,8-2 mm
Primo fiore CONCIA ALL'ANILINA
EN1021-1/2

USE AND CARE

For a proper maintenance of the products and to maintain unchanged the characteristics of the materials, we recommend to follow some very simple care instructions.

FABRICS

Cleaning: check the dedicated selection written on the color Swatch card. Usage: it is recommended to pay attention to the fabrics as they can be easily cut or ripped.

LEATHERS

Cleaning: clean with a wet white cloth with water. We recommend to use high quality products for the cleaning of the leather and to follow carefully the instructions of the manufacturer. In doubt, try out the product on a hidden part and wait at least 24 hours for the occurrence of any problems. Usage: remember that the leather is a delicate material therefore it is recommended to pay particular attention while using.

WOODS

Cleaning: clean with a soft and wet cloth with warm water. We always recommend to dry immediately after the cleaning process. All liquids or other residue must be removed in order to avoid the absorption. Usage: wooden surfaces, being a natural material, could be affected by an alteration of the color shade during time and use. We also remind that wooden surfaces cannot bear with high temperatures if placed directly on the wooden top.

METALS

Cleaning: both steel or aluminum surfaces, and painted ones, must be cleaned with a soft and wet cloth with hot water. For the most persistent stains, a small amount of liquid soap diluted in water may be used. We always recommend to dry immediately with a soft cloth or a leather one after the cleaning process. Never using cleaning products for steel, chlorine, bleach or other strong detergents. It is not recommended to use abrasive creams, score pads and abrasive sponges that can scratch the metal surfaces. Usage: pay attention to the stains of food such as coffee, coke, fruit juices that can leave indelible marks on the surface

WARRANTY

QUINTI guarantees the products will maintain their properties for 6 years from delivery, except normal usury and provided that they will be used according to the guidelines given. QUINTI will replace, free of charge, any product found non-compliant with this warranty, without incurring any other liability of sort. Components, external accessories or materials supplied by the buyer and applied to the products in order to customize them will not be supported by the guarantee. For an optimal maintenance of the products and to keep unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.them.